



Contents

Version 9.0.7 2026-05-07	2
Version 9.0.6 2026-02-24	2
Version 9.0.5 2025-07-18	2
Version 9.0.4 2025-04-24	3
Version 9.0.3 2025-02-24	3
Version 9.0.2 2024-08-29	4
Version 9.0.1 2024-02-26	4
Version 9.0.0 2024-01-10	5
Version 8.9.9 2023-06-02	6
Version 8.9.8 2022-08-19	6
Version 8.9.7 2022-06-20	6
Version 8.9.6 2022-03-24	7
Version 8.9.4 2021-06-01	8
Version 8.9.3 2021-02-01	8
Version 8.9.2 2020-10-30	8
Version 8.9.1 2020-06-24	9
Version 8.9.0 2020-06-15	9
Version 8.8.0 2020-03-24	9



GV-IP Device Utility Version History

Version 9.0.7 2026-05-07

Fixed:

- Failure to update GV-IS1320 firmware

Modified:

- Cybersecurity enhanced
- File manager UI for firmware file access updated to reduce the risk of accidental modification or deletion of important files

Version 9.0.6 2026-02-24

New:

- New features for GV-G Series cameras, GV-TMEB5800, and GV-BX2802 / 4802
 - Configuration changes supported across subnets
 - Support for Auto Set IP Address, even when cameras have IP conflicts
- Support for assigning camera channels from GV-Recording Server to GV-IP Decoder Box models

Modified:

- Multi-screen layout assignment disabled by default for GV-IP Decoder Box Mini

Version 9.0.5 2025-07-18

New:

- Support for the following IP camera models: GV-CBL2800, GV-CEB2800, GV-CEB4811, GV-CBL4811, GV-TNVR1620-P, and GV-TXVL1610
- Support for the following functions for exporting device details (Tool > Export device for optional functions)
 - Firmware version included
 - Addition of the export format CSV



Modified:

- Irrelevant S/N details removed for GV-G Series cameras, GV-TMEB5800, and GV-BX2802 / 4802 in exported device details (Tool > Export device for optional functions)

Version 9.0.4 2025-04-24

New:

- Support for the LPR camera: GV-LPR2812-DL

Version 9.0.3 2025-02-24

New:

- Support for the intercom controller: GV-IA1330
- Support for automatic device search through the PC with multiple network interface cards

Fixed:

- Issue with incorrect daylight-saving time on cameras after Sync Time with PC is applied
- Issue with the utility being unable to locate some devices when the PC installed with the utility have two different network sections set in a single network interface card

Modified:

- Internal Temperature function removed
- Daylight-saving time enabled automatically on cameras when Sync Time with PC is applied
- Cybersecurity enhanced



Version 9.0.2 2024-08-29

New:

- Support for the IP camera: GV-RMS32810
- Support for 16-division view for GV-IP Decoder Box Optimal

Fixed:

- Issue with missing VCRUNTIME140.dll after installing GV-IP Device Utility V9.0.1

Modified:

- Codec settings removed

Version 9.0.1 2024-02-26

New:

- Support for the following SNVR:
 - GV-RNVR256G0-N
- Support for configuration file export / import for the following IP cameras:
 - GV-BX2802
 - GV-BX4802
 - GV-GBL4900 / 4911
 - GV-GDR4900
 - GV-GEB4900
 - GV-GEBF4911
 - GV-GVD4910
 - GV-PBL8800
 - GV-PDR8800
 - GV-PFER12800
 - GV-RBL5800 / 5811
 - GV-REB5800
 - GV-RFER12700
 - GV-TMEB5800



Fixed:

- System not responding when clicking Configure for partial GV-SNVR and GV-IP camera models
- Connect setting function error for GV-IP Decoder Box Optimal and GV-IP Display 116

Version 9.0.0 2024-01-10

New:

- Support for new model GV-PFER12800
- Support for importing or exporting device settings for the following cameras with import/export password protection:

Firmware V1.05 to V 1.07	Firmware V1.05 to V1.07	Firmware V1.02 to V1.03	Firmware V1.03 to V1.04
GV-BLFC5800	GV-EBD8800	GV-PTZ5810-IR	GV-SD4834-IR
GV-EBD4704	GV-EBD8813		GV-SD4825-IR
GV-EBD4813	GV-EBDP5800		
GV-EBFC5800	GV-FER5702		
GV-TBL4705	GV-TBL8804		
GV-TBL4807	GV-TBL8810		
GV-TBL4810	GV-TBLP5800		
GV-TDR4704	GV-TDR8805		
GV-TDR4803	GV-TVD8810		
GV-TFD4800			
GV-TVD4810			
GV-TVD4811			



Version 8.9.9 2023-06-02

New:

- Support for online firmware upgrade for the following IP camera models:
 - GV-BX2802 / 4802
 - GV-PBL8800
 - GV-PDR8800
 - GV-TMEB5800

Modified:

- Firmware upgrade pop-up message modified

Fixed:

- Issue with loading incorrect live view loop time interval after setting the layout on GV-IP Device Utility

Version 8.9.8 2022-08-19

New:

- Support for these IP camera models: GV-TMEB5800, GV-BX2802, GV-BX4802

Version 8.9.7 2022-06-20

New:

- Support for these IP camera models: GV-PBL8800 and GV-PDR8800

Modified:

- Redundant audio files removed



Version 8.9.6 2022-03-24

New:

- Support for displaying the serial number of the following models:
 - GV-ABL / TBL Series
 - GV-ADR / TDR Series
 - GV-AVD / TVD Series
 - GV-BLFC5800
 - GV-EBD Series
 - GV-EBFC5800
 - GV-FER5702
 - GV-PTZ5810-IR
 - GV-SD2322-IR / SD2722-IR / SD3732-IR / SD4825-IR / SD4834-IR
 - GV-TFD Series
- Support for exporting host list txt files documenting the serial number of the following models:
 - GV-ABL / TBL Series
 - GV-ADR / TDR Series
 - GV-AVD / TVD Series
 - GV-BLFC5800
 - GV-EBD Series
 - GV-EBFC5800
 - GV-FER5702
 - GV-PTZ5810-IR
 - GV-SD2322-IR / SD2722-IR / SD3732-IR / SD4825-IR / SD4834-IR
 - GV-TFD Series



Version 8.9.4 2021-06-01

New:

- Support for GV-QFER12700

Fixed:

- Inability to change the default PW using the Utility, for the first-time use of the following models: GV-ADR2702 / ADR4702 / ABL2703 / ABL4703 / TDR2702 / TDR4702 / TBL2703 / TBL4703 / TVD4700 / TVL4700

Version 8.9.3 2021-02-01

New:

- Support for new models: GV-IP Display 101 and GV-FR Panel
- Support for device names of up to 32 characters for GV-IP Decoder Box Ultra or GV-IP Display 101
- Support for dual stream from GV-IP Decoder Box Ultra
- Support for applying one login credential to all devices in the same tab under Dispatch Pattern
- Support for importing the recognition engine to GV-LPR2800-DL and GV-LPR2811-DL
- Support for configuring the Loop Time Interval and Stream Mode of GV-IP Decoder Box Ultra or GV-IP Display 101

Version 8.9.2 2020-10-30

Changed:

- Audio codec changed to MP3



Version 8.9.1 2020-06-24

New:

- Support for configuring the password of the following devices upon first-time login (Note: To configure the password of the devices all at once, it is required to connect to a LAN with a DHCP server):
 - GV-ADR2702 / 4702, GV-ABL2703 / 2703, GV-EBD8700, GV-TBL2703 / 4700 / 4703, GV-TDR2702 / 4702, GV-TVD4700 firmware V1.02 or later
 - GV-ABL2702 / 4712, GV-AVD2700 / 4710, GV-EBD2702, GV-TBL4710, GV-TDR2700, GV-TVD4710 firmware V1.04 or later
 - GV-ABL4701, GV-ADR4701, GV-EBD4700 / 4711, GV-TDR4700 firmware V1.07 or later
 - GV-ABL8712, GV-AVD8710, GV-EBD8711, GV-TBL8710, GV-TVD8710 firmware V1.03 or later

Version 8.9.0 2020-06-15

New:

- Support for new models: GV-QSD5730 / QSD5731-IR

Version 8.8.0 2020-03-24

New:

- Support for “Upgrade all devices” function to upgrade the firmware of the following devices in batches:
 - GV-AS210 / 2110 / 2120 / 410 / 4110/ 4111 / 810 / 8110 / 8111 firmware V2.20 or later
 - GV-AS1520 firmware V2.03 or later
 - GV-AS1620 firmware V1.00 or later
 - GV-FWC firmware V1.00 or later
 - GV-I/O Box 4 Ports firmware V2.05 or later
 - GV-I/O Box 8/16 Ports firmware V2.04 or later